

Description

Double (2 Doors) 2 Window Glass Barn Door with black metal frame suitable for any wall-mounted application. Available in clear or frosted glass. Frosted (privacy) glass ideal for bathrooms or other areas requiring visual privacy. See dimensional drawing for sizing recommendations. Suitable for use in both professional and residential applications.

Frame

Proprietary aluminum extrusion finished in matte black industrial-strength powder coat suitable residential or commercial applications. 1" wide x 1-1/4" thick frame size. No visible screws or fasteners.

Glass


Full 1/4in thick, tempered for strength and safety. Clear or Frosted (Acid Etch.)

Track & Hardware

All parts are precision-made steel construction, finished in matte black industrial-strength powder coat. Track is 1-1/2in tall, 1/4in thick. Oversized roller wheels ensure the smoothest roll possible. Adjustable door stops (left + right) can be placed at any point along the track. Small floor guides provided to keep the doors aligned. Anti-jump feature prevents door from coming off track. All necessary mounting screws and hardware included for installation and operation. Optional soft open/close feature available utilizing our spring-loaded mechanism that enables a soft, quiet functionality.


Handle Options

13in Square Cast Iron (Black) Pull




Suggested on Front

13in Offset Cast Iron (Black) Pull



Suggested on Front



13in Flat (Black) Pull



Suggested on Rear

Kickplate Option

Black steel powder coated to match door frame. 10in from bottom of door.

No Kickplate With Kickplate

Part Number

Made in the USA.

B22							
Double 2 Window Black Metal Frame	Width of Each Door (inches)	Height of Each Door (inches)	Glass Type C - Clear F - Frosted	Kickplate N - None K - Kickplate	Front Handles N - None S - 13in Square F - 13in Offset	Rear Handles N - None T - 13in Flat S - 13in Square F - 13in Offset	Soft Open/Close N - None S - Soft Open/Close

PROJECT

QTY

TYPE